

Jednotky kondenzační – Cubigel compressors R-404A, 507 HMBP

Pro použití s expanzním ventilem.
 Rozsah teplot HMBP -25 °C až +10 °C.
 Napájecí napětí 220-240 V/50 Hz.
 Napájecí napětí 400 V/50 Hz.

Provedení:
 3 N – servisní ventily, se sběračem

Typ	HP	Válec cm ³	Příkon T ₀ +7,2 °C		Chladicí výkon W (T ₀) T ₁₁ +32 °C, T _k +55 °C			Rozměry mm			Hmotnost kg
			A	W	-15	-10	-5	Šířka	Délka	Výška	
CML 45 TB 3N	1/5	4,50	2,19	385	300	361	427	325	425	235	14,6
CML 60 TB 3N	1/4	5,67	2,77	477	409	491	579	330	425	245	22,5
CML 80 TB 3N	3/8	7,57	3,27	570	567	672	794	355	450	270	24
CML 90 TB 3N	3/8	8,80	3,98	700	646	775	913	355	425	270	23,9
CMP 12 TB 3N	1/2	12,00	4,05	860	899	1 081	1 279	425	480	350	29,8
CMP 14 TB 3N	1/2	14,00	4,86	1 000	973	1 173	1 387	425	500	350	29,9
CMX 18 TB 3M	7/8	18,40	6,98	1 370	1 206	1 424	1 648	430	500	350	33,0
CMX 21 TB 3N	1	20,72	6,85	1380	1 270	1 518	1 798	455	500	440	36,0
CMS 26 TB 3N	1 3/8	25,95	8,73	1738	1 855	2 222	2 612	455	515	440	43,7
CMS 26 T3 3N-400 V	1 3/8	25,95	3,4	2180	1 855	2 222	2 612	455	515	440	43,7
CMS 34 TB 3N	1 5/8	34,25	12,06	2 424	2 424	2 959	3 480	455	515	440	45,3
CMS 34 T3 3N	1 5/8	34,25	5,04	3 047	2 597	2130	3 511	455	515	440	44

Pokračování

Typ	Vývody			Registr. číslo
	Sání		Výtlač	
CML 45 TB 3N	3/8F	servisní ventil	1/4F	7153000.509
CML 60 TB 3N	3/8F	servisní ventil	1/4F	7153000.510
CML 80 TB 3N	3/8F	servisní ventil	1/4F	7153000.508
CML 90 TB 3N	3/8F	servisní ventil	3/8F	7153000.511
CMP 12 TB 3N	3/8F	servisní ventil	3/8F	7153000.512
CMP 14 TB 3N	3/8F	servisní ventil	3/8F	7153000.513
CMX 18 TB 3N	3/8R	servisní ventil Rotalock	3/8R	7153000.515
CMX 21 TB 3N	3/8R	Rotalock	3/8R	7153000.516
CMS 26 TB 3N	1/2R	Rotalock	3/8R	7153000.518
CMS 26 T3 3N-400 V	5/8R	Rotalock	3/8R	7153000.519
CMS 34 TB 3N	5/8R	Rotalock	3/8R	7153000.522
CMS 34 T3 3N	5/8R	Rotalock	3/8R	7153000.523

