

7.2 Filtry sací – FC

BURN OUT FILTER DRIER (filtry pro spáleniny)

Šroubovací

Typ	Vývody		Délka mm	Registr. číslo
	inch	mm		
SRE – 084	1/2	12	130	7242000.830C
SRE – 163	3/8	10	158	7242000.831C
SRE – 164	1/2	12	158	7242000.832C
SRE – 165	5/8	16	164	7242000.833C
SRE – 414	1/2	12	250	7242000.834C
SRE – 415	5/8	16	250	7242000.835C
SRE – 416	3/4	18	250	7242000.836C

Pájecí

Typ	Vývody		Délka mm	Registr. číslo
	inch	mm		
SRE – 084	1/2	12	130	7242000.816C
SRE – 163	3/8	10	158	7242000.817C
SRE – 164	1/2	12	158	7242000.818C
SRE – 165	5/8	16	164	7242000.819C
SRE – 415	5/8	16	250	7242000.820C
SRE – 416	3/4	18	250	7242000.821C
SRE – 166	3/4	18	164	7242000.822C
SRE – 167	7/8	22	225	7242000.823C
SRE – 307	7/8	22	230	7242000.824C
SRE – 417	7/8	22	250	7242000.825C
SRE – 419	11/8	28	250	7242000.826C



Dehydrátory obousměrné pro kapalně chladivo (Bi-Flow) – FC

Určeno pro okruh tepelného čerpadla s chladivem R-134a, R-407C a R-410A

Typ	Vývody	Registr. číslo
SRS 083 S	10 mm	7240000.502C
SRS 084 S	12 mm	7240000.503C
SRS 165 S	16 mm	7240000.504C
SRS 167 S	22 mm	7240000.505C
SRS 165	16 mm	7240000.510C

