

2.1.2 Kompresory – Cubigel compressors R-600a LBP

Hermetické kompresory pro použití s kapilárou.

Rozsah teplot LBP -35 °C až -10 °C.

Napájecí napětí 220-240 V/50 Hz.

Typ	HP	Chladicí výkon W $T_o -25\text{ °C}, T_k +55\text{ °C}$	Cena Kč/1 ks	Registr. číslo
HSH 80AA	1/9	81	1 475,00	7153000.846M
HQY 70AA	1/8	98	1 540,00	7153000.842
HQY 80AA	1/7	120	1 640,00	7153000.843
HQY 90AA	1/6	134	1 675,00	7153000.844
HQY 99AA	1/6	144	1 730,00	7153000.845
HQM 12AA	1/5	170	2 000,00	7153000.445
HPY 14AA	1/5	166	2 015,00	7153000.447
HPY 16AA	1/4	181	2 150,00	7153000.448



Kompresory – Cubigel compressors R-290 HMBP

Hermetické kompresory pro použití s kapilárou a TEV.

Rozsah teplot HMBP -25 °C až +10 °C.

Napájecí napětí 220-240 V/50 Hz.

Typ	HP	Chladicí výkon W $T_o -10\text{ °C}, T_k +55\text{ °C}$	Cena Kč/1 ks	Registr. číslo
NLY 45RAa	1/5	609	2 405,00	7153000.540
NLY 60RAa	1/4	829	2 455,00	7153000.542
NL 80TB	3/8	948	2 535,00	7153000.544
NLY 90RAa	3/8	1 244	2 715,00	7153000.546
NPY 12RAa	1/2	1 728	2 975,00	7153000.548
NX 18TB	3/4	2 320	4 925,00	7153000.550
NX 21TB	7/8	2 650	5 055,00	7153000.552

